

42-009-01954

Please Refer
to File No. _____

**RAILROAD COMMISSION OF TEXAS
OIL AND GAS DIVISION**

Form 2A
Application
To Plug and
Well Record

FILE IN DUPLICATE WITH DEPUTY SUPERVISOR OF DISTRICT IN WHICH
WELL IS LOCATED FIVE FULL DAYS PRIOR TO PLUGGING

Company Champlin Oil & Refining Co. Address P. O. Box 1797 - Midland, Texas

Sec. No. 5 Block No. 1 Survey University Lands County Andrews

Well No. 4 (LT & UT) Name of Lease University "L" (13655) No. of Acres 314 Elev. 3177 DF

Name of Field in which well is located University Block 9 (Wolfcamp) & (Pennsylvanian)

Located 5 Miles south Direction from Andrews, Texas (Nearest P. O. or Town)

Form 1, "Notice of Intention to Drill," was filed in name of Champlin Oil & Refining Co.

Drilling Commenced April 4, 19 59, Drilling Completed May 13, 19 59

Has this well ever produced Oil? Yes or Gas? Yes

Character of Well (Oil, Gas or Dry) Oil Total Depth 9100'

Date you wish to Plug September 30, 19 64.

Name of Party Plugging Well Holliburton Address Andrews, Texas

Correspondence regarding this well should be sent to: Name Champlin Oil & Refining Co.

Address P. O. Box 1797 - Midland, Texas

Initial Production of Gas: Volume (MCF) 172 (LT) 93 (UT) 24 hrs. Pressure 14.65 lbs. per square inch

Initial Production of Oil: Barrels 195 (LT), 181 (UT)

Give notice before Plugging to all available Lease Owners, as required by Rule (10)

When Plugging completed, file final Plugging Report, duly signed and sworn to. All necessary forms will be furnished by the Deputy Supervisor of district in which well is located.

NOTE: If no log available, so state and give all information that can be obtained to as total depth of hole, or not cemented, producing formation, water sands, and as near as possible date well was drilled.

UNIVERSITY LANDS
Approved _____
Answer _____ File _____
REC'D SEP 25 1964
Refer to _____
Please Answer _____
Road and Return _____

General Remarks: 13-3/8" set at 331' and cemented to surface - 9-5/8" set at 4749' and cemented to surface, & 7" set at 9099' cemented w/400 sx. Two strings of 2-3/8" at 8850' & 8625'. Cement plugs will be set across all open perforations and at bottom of 9-5/8" casing. Cement plug will also be set at top of hole.
FILL OUT FORMATION AND AFFIDAVIT ON REVERSE SIDE

