



Texas Commission
on Environmental Quality
Surface Casing Program

DEPTH OF USABLE-QUALITY GROUND WATER TO BE PROTECTED

Date **January 28, 2011**

TCEQ File No.: SC- **14063**

***** EXPEDITED APPLICATION *****

API Number **00333407**

Attention: **SETH SANDERS**

RRC Lease No. **000000**

SC_748011_00333407_000000_14063.pdf

SANDRIDGE E&P LLC
123 ROBERT S KERR
OKLAHOMA CITY OK 73102

P-5# 748011

--Measured--

560 ft FWL

1750 ft FNL

MRL: SECTION

Digital Map Location:

X-coord/Long **102.71503**

Y-coord/Lat **32.14973**

Datum **83**

Zone

County **ANDREWS**

Lease & Well No. **UNIVERSITY 20 #1**

Purpose **ND**

Location **SUR-UL, BLK-10, SEC-20, -- [TD=6630] , [RRC 8] ,**


To protect usable-quality ground water at this location, the Texas Commission on Environmental Quality recommends:

The interval from the land surface to a depth of 250 feet
and the zone from 800 feet to 1300 feet must be protected.

Note: Unless stated otherwise, this recommendation is intended to apply only to the subject well and not for area-wide use. Approval of the well completion methods for protection of this groundwater falls under the jurisdiction of the Railroad Commission of Texas. **This recommendation is intended for normal drilling, production, and plugging operations only. It does not apply to saltwater disposal operation into a nonproductive zone (RRC Form W-14).**

If you have any questions, please contact us at 512-239-0515, sc@tceq.state.tx.us, or by mail MC-151.


Sincerely,


Digitally signed by Jack Oswalt
DN: c=US, st=Texas, l=Austin, ou=Surface
Casing, o=Texas Commission on
Environmental Quality, cn=Jack Oswalt,
email=joswalt@tceq.state.tx.us
Date: 2011.01.28 09:09:20 -06'00'

Jack M. Oswalt, P.G.

Geologist, Surface Casing Team
Waste Permits Division

GEOLOGIST SEAL



The seal appearing on this document was authorized by Jack M. Oswalt on 1/28/2011
Note: Alteration of this electronic document will invalidate the digital signature.