

ST. ANDREWS

UNIVERSITYBRITTANY #2

Location:	
API #:	42-003-41338
Field:	Saint Wilma (Strawn)
Footage:	660' FNL and 745' FWL
Sec, Blk:	11, 3
Srvy, County:	UL, Andrews County
Elevations:	
GL:	3065
KB:	3081
KB Calc:	16

[illegible]

Tubing Detail (bottom to top)			
Joints	Description	Length	Depth
271	2-3/8" J-55 jts	8,576.65	8,576.65
1	2-3/8" Enduro blast jt	31.61	8,608.26
1	2-3/8" SN	1.10	8,609.36
1	2-3/8" x 5-1/2" TAC	2.70	8,612.06
1	2-3/8" x 3-1/2" Slotted mud jt	30.00	8,642.06
275			8,642.06

Rod Detail (bottom to top)			
Rods	Description	Length	Depth
1	1-1/2" x 26' SMPR PR	26	26.00
6	7/8" x 2' x 4' Pony rods	6	32.00
117	7/8" Sucker rods	2925	2957.00
216	3/4" Sucker rods	5400	8357.00
8	1-1/2" K-bars	200	8557.00
1	1-3/4" x 4' stabilizer	4	8561.00
1	2" x 1-1/2" x 20' pump	20	8581.00
1	1 x 20' gas anchor		
			8581.00

No. jts	Casing Detail	Length	Depth
	FLOAT SHOE	1.20	11198.80
1	5 -1/2" 17# L-80, LTC	19.27	11179.53
	FLOAT COLLAR	1.34	11178.19
30	5 -1/2" 17# L-80, LTC	1158.62	10019.57
1	5 -1/2" 17# L-80, LTC MARKER	18.62	10000.95
56	5 -1/2" 17# L-80, LTC	2165.43	7835.52
1	5 -1/2" 17# L-80, LTC MARKER	18.70	7816.82
91	5 -1/2" 17# L-80, LTC BOND COATED	3509.94	4306.88
113	5 -1/2" 17# L-80, LTC	4344.92	-38.04
293	Total Pipe	11184.00	

Updated: 3/11/2011

By: LKS

Hole Size:	12-1/4"
Surf csg :	9-5/8", 36#, Grd
Set @:	1882'
Cmt Lead:	700 sxs, C, 13.5, 1.77
Cmt Tail:	200 sxs, C, 14.8, 1.32
Circ:	Yes, 44 sxs

5-1/2" Csg TOC @ 4650'

8668' - 8932' (51 Holes)	9
9012' - 9196' (55 Holes)	8
9394' - 9584' (54 Holes)	7
9735' - 9755' (80 Holes)	6
9940' - 9960' (80 Holes)	5
10101' - 10126' (100 Holes)	4
10412' - 10646' (53 Holes)	3
10730' - 10922' (52 Holes)	2
11070' - 11100' (120 Holes)	1

Hole Size:	7-7/8" & 8-3/4"
Prod. Csg:	5-1/2", 17#, L-80
Set @:	11184
Cmt w/ Lead:	800 sxs, H 35:65, 12.4, 2.05
Tail:	800 sxs, H 50:50, 14.2, 1.28

Log PBTD	11126'
Drillers TD	11200'

