

OLD COURSE

Hole Size:	12-1/4"
Surf csg :	9-5/8", 36#, Grd J-55
Set @:	1880
Cmt Lead:	650sxs Class C, 13.5, 1.77
Cmt Tail:	200 sxs Class C, 14.8, 1.35
Circ:	35 SXS

Location:	
API #:	42-003-42136
Field:	Saint Wilma (Strawn)
Footage:	1650' FSL & 990' FWL
Sec. Blk:	BLK 4, Sec 39, 8.7 miles NE direction from Andrews
Srvy. County:	Andrews County, Texas
Elevations:	
GL:	3077
KB:	16
KB Calc:	

[illegible]

Detail (Top to Bottom)			
Joints	Description	Length	Depth
299	2-3/8" J-55 tbg	9,217.00	9,217.00
1	1 Alloy endure jt	32.10	9,249.10
1	SN	1.10	9,250.20
1	1 AC	2.75	9,252.95
1	3-1/2" x 2-3/8" MJ	30.30	9,283.25
			9,283.25
	EOT @		9,283.25

Detail (Top to Bottom)			
Rods	Description	Length	Depth
1	SPMPR	26	26.00
2	7/8" x 2' x8'	10	36.00
126	7/8" rods	3150	3,186.00
234	3/4" rods	5850	9,036.00
8	1-1/2" K bars x 3-1/2" pin	200	9,236.00
1	3/4 x 4' stabilizer	4	9,240.00
1	2" x 1-1/4" x 20' pump	20.00	9,260.00
1	1" x 20' gas anchor	20.00	9,280.00
			9,280.00
	TOTAL		9,280.00

	Casing Detail	Length	Depth
	FLOAT SHOE	1.65	11200.00
	5 -1/2" 17# L-80, LTC	18.42	11181.58
	FLOAT COLLAR	1.31	11180.27
	5 -1/2" 17# L-80, LTC	1157.81	10022.46
	5 -1/2" 17# L-80, LTC MARKER	19.09	10003.37
	5 -1/2" 17# L-80, LTC	2159.57	7843.80
	5 -1/2" 17# L-80, LTC MARKER	18.60	7825.20
	5 -1/2" 17# L-80, LTC BOND COAT	3470.22	4354.98
	5 -1/2" 17# L-80, LTC	4363.25	-8.27
	Total Pipe	11209.92	

5-1/2" Csg TOC @ 4,750'

Pump Intake@	9,250.20
--------------	----------

9,406-44' (80 holes)

9,656-94' (80 holes)

9,842-62' (100 holes)

9,983-10,088' (100 holes)

10,086-354' (48 holes)

10,416-446' (80 holes)

10,636-674' (80 holes)

10,736-866' (60 holes)

11,010-11,044' (80 holes)

Hole Size:	7 7/8"
Prod. Csg:	5-1/2", 17#, L-80
Set @:	11,200
Cmt w/ Lead:	sxs, 65:35 H, 12.4, 2.05
Tail:	sxs, 50:50 H, 14.2, 1.28

Updated:	3/1/2011	By: MG
----------	----------	--------

C:\Users\ljimenez\AppData\Local\Microsoft\Windows\Temporary Internet Files\Content.Outlook\WQZPIU07\UniversityCarrie #3 - Well History (ULS).xls]WBD

PBTD	11,139
Drillers TD	11,200