

Type or print only

RAILROAD COMMISSION OF TEXAS  
Oil and Gas Division  
Notice of Intention to Plug and Abandon

Form W-3A

Rev 1/1/83

(02/00)

WWW-1

Operators must comply with RRC plugging procedures as outlined on the reverse side.

|  |                            |   |  |
|--|----------------------------|---|--|
| <b>1. Operator's Name and Address (Exactly as shown on Form P-5, Organization Report)</b><br>DEVON ENERGY PRODUCTION CO, L.P.<br>ATTN HEATHER LACY<br>333 WEST SHERIDAN AVE<br>OKLAHOMA CITY, OK 73102-        |                            | <b>3. RRC District No.</b><br>08                    | <b>4. County of Well Site</b><br>CRANE |
|  |                            | <b>5. API No.</b><br>42- 10300320                   | <b>6. Drilling Permit No.</b>          |
| <b>2. RRC Operator Number</b> 216378   | <b>7. Rule 37 Case No.</b> | <b>8. Oil Lease No. or Gas Well ID No.</b><br>11218 | <b>9. Well No.</b><br>9                |
|  |                            |   |  |
| <b>10. Field Name (Exactly as shown on RRC records)</b><br>DUNE  |                            | <b>11. Lease Name</b><br>STATE -EF-                 |  |
| <b>12. Location</b><br>• Section No. 10 Block No 30 Survey and Survey No ULS Abstract No. A-<br>• Distance (in miles) and direction from a nearby town in this county (name the town). 10 MILES NORTH OF CRANE |                            |   |  |
| <b>13. Type of well</b><br>Oil   |                            | <b>14. Type of completion</b><br>Single             | <b>15. Total depth</b><br>3915         |

**16. Usable-quality water strata detail**

Letter Date

**17. •If there are wells in this area which are producing from or have produced from a shallower zones, state depth of zones**

\_\_\_\_\_, \_\_\_\_\_, \_\_\_\_\_, \_\_\_\_\_, \_\_\_\_\_, and \_\_\_\_\_.

**• If there are wells into which salt water is being or has been disposed of into a shallower zones, state depth of zones**

\_\_\_\_\_, \_\_\_\_\_, \_\_\_\_\_, \_\_\_\_\_, \_\_\_\_\_, and \_\_\_\_\_.

Top of cement determined by

[illegible]

| Liner size | Top of liner | Bottom of liner | Packer setting depth |
|------------|--------------|-----------------|----------------------|
|            |              |                 |                      |
|            |              |                 |                      |
|            |              |                 |                      |
|            |              |                 |                      |

**19. Has notice of intent to plug been filed previously for this well?** No **Date:**

21. Record of perforated intervals or open hole

Perforations or Open Hole

Perforations

Interval (ft)

3884

to

3705

Plugged or Not Plugged

Not Plugged

Historic Plug Information

Set at

feet with

feet of cement on top

feet to

feet with

sacks

Sacks pumped 'on top'

Sacks pumped 'below'

Other Plugging proposal type

Perforations or Open Hole

Interval (ft)

to

Plugged or Not Plugged

Historic Plug Information

Set at

feet with

feet of cement on top

feet to

feet with

sacks

Sacks pumped 'on top'

Sacks pumped 'below'

Other Plugging proposal type

Perforations or Open Hole

Interval (ft)

to

Plugged or Not Plugged

Historic Plug Information

Set at

feet with

feet of cement on top

feet to

feet with

sacks

Sacks pumped 'on top'

Sacks pumped 'below'

Other Plugging proposal type

Perforations or Open Hole

Interval (ft)

to

Plugged or Not Plugged

Historic Plug Information

Set at

feet with

feet of cement on top

feet to

feet with

sacks

Sacks pumped 'on top'

Sacks pumped 'below'

Other Plugging proposal type

21. Record of perforated intervals or open hole

Perforations or Open Hole

Interval (ft)

to

Plugged or Not Plugged

Historic Plug Information

Set at

feet with

feet of cement on top

feet to

feet with

sacks

Sacks pumped 'on top'

Sacks pumped 'below'

Other Plugging proposal type

Perforations or Open Hole

Interval (ft)

to

Plugged or Not Plugged

Historic Plug Information

Set at

feet with

feet of cement on top

feet to

feet with

sacks

Sacks pumped 'on top'

Sacks pumped 'below'

Other Plugging proposal type

Perforations or Open Hole

Interval (ft)

to

Plugged or Not Plugged

Historic Plug Information

Set at

feet with

feet of cement on top

feet to

feet with

sacks

Sacks pumped 'on top'

Sacks pumped 'below'

Other Plugging proposal type

Perforations or Open Hole

Interval (ft)

to

Plugged or Not Plugged

Historic Plug Information

Set at

feet with

feet of cement on top

feet to

feet with

sacks

Sacks pumped 'on top'

Sacks pumped 'below'

Other Plugging proposal type

**20. Plugging proposal (List all bridge and cement plugs. Load the hole with at least 9.5 lbs. per gallon mud.)**

|                         |      |                |      |                          |     |                       |    |       |
|-------------------------|------|----------------|------|--------------------------|-----|-----------------------|----|-------|
| Plugging Proposal Type  | CIBP | Set at or from | 3655 | feet to                  |     | feet with             | 25 | sacks |
|                         |      |                |      | feet with                | 100 | feet of cement on top |    |       |
| Additional requirements |      |                |      | sacks pumped 'below' and |     | sacks pumped 'on top' |    |       |
| 6 - None                |      |                |      |                          |     |                       |    |       |

|   |             |                |      |                          |      |                       |    |       |
|---|-------------|----------------|------|--------------------------|------|-----------------------|----|-------|
| Plugging Proposal Type  | Cement Plug | Set at or from | 2000 | feet to                  | 1900 | feet with             | 45 | sacks |
|   |             |                |      | feet with                |      | feet of cement on top |    |       |
|   |             |                |      | sacks pumped 'below' and |      | sacks pumped 'on top' |    |       |
| Additional requirements   |             |                |      |                          |      |                       |    |       |
| 2 - Perforate and Squeeze, 4 - Wait 4 hours and tag top of plug |             |                |      |                          |      |                       |    |       |

|   |             |                |      |                          |      |                       |    |       |
|---|-------------|----------------|------|--------------------------|------|-----------------------|----|-------|
| Plugging Proposal Type  | Cement Plug | Set at or from | 1150 | feet to                  | 1050 | feet with             | 45 | sacks |
|   |             |                |      | feet with                |      | feet of cement on top |    |       |
|   |             |                |      | sacks pumped 'below' and |      | sacks pumped 'on top' |    |       |
| Additional requirements   |             |                |      |                          |      |                       |    |       |
| 2 - Perforate and Squeeze, 4 - Wait 4 hours and tag top of plug |             |                |      |                          |      |                       |    |       |

|   |             |                |     |                          |     |                       |    |       |
|---|-------------|----------------|-----|--------------------------|-----|-----------------------|----|-------|
| Plugging Proposal Type  | Cement Plug | Set at or from | 890 | feet to                  | 790 | feet with             | 45 | sacks |
|   |             |                |     | feet with                |     | feet of cement on top |    |       |
|   |             |                |     | sacks pumped 'below' and |     | sacks pumped 'on top' |    |       |
| Additional requirements   |             |                |     |                          |     |                       |    |       |
| 2 - Perforate and Squeeze, 4 - Wait 4 hours and tag top of plug |             |                |     |                          |     |                       |    |       |

|   |             |                |     |                          |     |                       |    |       |
|---|-------------|----------------|-----|--------------------------|-----|-----------------------|----|-------|
| Plugging Proposal Type  | Cement Plug | Set at or from | 650 | feet to                  | 550 | feet with             | 45 | sacks |
|   |             |                |     | feet with                |     | feet of cement on top |    |       |
|   |             |                |     | sacks pumped 'below' and |     | sacks pumped 'on top' |    |       |
| Additional requirements   |             |                |     |                          |     |                       |    |       |
| 2 - Perforate and Squeeze, 4 - Wait 4 hours and tag top of plug |             |                |     |                          |     |                       |    |       |

|                           |                     |                |     |                          |   |                       |    |       |
|---------------------------|---------------------|----------------|-----|--------------------------|---|-----------------------|----|-------|
| Plugging Proposal Type    | Cement Surface Plug | Set at or from | 350 | feet to                  | 0 | feet with             | 90 | sacks |
|                           |                     |                |     | feet with                |   | feet of cement on top |    |       |
|                           |                     |                |     | sacks pumped 'below' and |   | sacks pumped 'on top' |    |       |
| Additional requirements   |                     |                |     |                          |   |                       |    |       |
| 2 - Perforate and Squeeze |                     |                |     |                          |   |                       |    |       |

|                         |  |                |  |                          |  |                       |  |       |
|-------------------------|--|----------------|--|--------------------------|--|-----------------------|--|-------|
| Plugging Proposal Type  |  | Set at or from |  | feet to                  |  | feet with             |  | sacks |
|                         |  |                |  | feet with                |  | feet of cement on top |  |       |
|                         |  |                |  | sacks pumped 'below' and |  | sacks pumped 'on top' |  |       |
| Additional requirements |  |                |  |                          |  |                       |  |       |

|                         |  |                |  |                          |  |                       |  |       |
|-------------------------|--|----------------|--|--------------------------|--|-----------------------|--|-------|
| Plugging Proposal Type  |  | Set at or from |  | feet to                  |  | feet with             |  | sacks |
|                         |  |                |  | feet with                |  | feet of cement on top |  |       |
|                         |  |                |  | sacks pumped 'below' and |  | sacks pumped 'on top' |  |       |
| Additional requirements |  |                |  |                          |  |                       |  |       |

20. Plugging proposal (List all bridge and cement plugs. Load the hole with at least 9.5 lbs. per gallon mud.)

Plugging Proposal Type

Set at or from

feet to

feet with

sacks

feet with

feet of cement on top

sacks pumped 'below' and

sacks pumped 'on top'

Additional requirements

Plugging Proposal Type

Set at or from

feet to

feet with

sacks

feet with

feet of cement on top

sacks pumped 'below' and

sacks pumped 'on top'

Additional requirements

Plugging Proposal Type

Set at or from

feet to

feet with

sacks

feet with

feet of cement on top

sacks pumped 'below' and

sacks pumped 'on top'

Additional requirements

Plugging Proposal Type

Set at or from

feet to

feet with

sacks

feet with

feet of cement on top

sacks pumped 'below' and

sacks pumped 'on top'

Additional requirements

Plugging Proposal Type

Set at or from

feet to

feet with

sacks

feet with

feet of cement on top

sacks pumped 'below' and

sacks pumped 'on top'

Additional requirements

Plugging Proposal Type

Set at or from

feet to

feet with

sacks

feet with

feet of cement on top

sacks pumped 'below' and

sacks pumped 'on top'

Additional requirements

API No:

10300320

Well No:

9

**22. Name and address of cementing  
company or contractor**

SUNSET WELL SERVICE, INC. PO BOX 7139, MIDLAND, TX 79708

**23. Anticipated plugging date for this well is:**

March 22 2019

Natalie Beavers

PRODUCTION TECHNOLOGIST

**Typed or printed name of operator's representative****Title of person**

(405) 552-3573

Natalie Beavers

**Telephone: Area Code Number****Signature****RRC District Office Action**

August 01 2019

Jeffery Morgan

**Expiration date****District Director****Must Witness:** No

Approved on behalf of the District Director by:

Erik Hanson