

150 00

RAILROAD COMMISSION OF TEXAS
OIL AND GAS DIVISION

MACK WALLACE, Chairman
JAMES E. (JIM) NUGENT, Commissioner
JOHN SHARP, Commissioner



JIM MORROW, P.E.
Director
JERRY W. MULLICAN
Director of Underground
Injection Control

1701 N. CONGRESS

CAPITOL STATION — P. O. DRAWER 12967

AUSTIN, TEXAS 78711-2967

PERMIT TO INJECT FLUID INTO A RESERVOIR
PRODUCTIVE OF OIL OR GAS

PROJECT NO. F 11469

Vinson Exploration
300 West Texas #330
Midland, TX 79701

Based on information contained in your application (Forms H-1 and H-1A) dated July 15, 1987, you are hereby authorized to use the following well to inject fluid into the Grayburg Formation:

Univ. "26-29" Lease, (09922), Well No. 2,
Bachelor Hill (Grayburg) Field, Crockett County, RRC District 7C

This authority is granted in accordance with Statewide Rule 46 of the Railroad Commission of Texas and subject to the following special and standard conditions:

SPECIAL CONDITIONS:

1. Fluid shall only be injected into strata in the subsurface depth interval from 1430 feet to 1645 feet.
2. The injection volume of salt water shall not exceed 130 barrels per day.
3. The maximum operating surface injection pressure shall not exceed 700 psig.
4. The authority to inject fluid is limited to the injection of salt water.

STANDARD CONDITIONS:

1. Fluid injection must be through tubing set on a packer.
2. The District Office must be notified 48 hours prior to:
 - a. running tubing and setting packer;
 - b. beginning any workover or remedial operation;
 - c. conducting any required pressure tests or surveys.
3. The wellhead must be equipped with a pressure observation valve on the tubing and for each annulus.
4. Prior to beginning injection, and subsequently after any workover, an annulus pressure test must be performed. The test pressure must equal the maximum authorized injection pressure or 500 psig, whichever is less, but must be at least 200 psig. The test must be performed and the results submitted in accordance with the instructions of Form H-5.

5. The injection pressure and injection volume must be monitored at least monthly and reported annually on Form H-10 to the Commission's Austin Office.
6. Within 30 days after completion, conversion to fluid injection, or any workover which results in a change in well completion, a new Form W-2 or G-1 must be filed in duplicate with the District Office to show the current completion status of the well and to show the current production test allowable to be transferred from converted wells to producing wells on the same lease. The date of the injection permit and the project number must be included on the new Form W-2 or G-1.
7. Written notice of intent to transfer the permit must be submitted to the Commission at least 15 days prior to the date the transfer will occur by filing Form P-4.
8. A well herein authorized cannot be converted to a producing well and have an allowable assigned without filing an amended Form W-1 and receiving Commission approval.
9. Unless otherwise required by conditions of this permit, completion and operation of the well shall be in accordance with the information represented on the application (Forms H-1 and H-1A).

Provided further that, should it be determined that such injection fluid is not confined to the approved strata, then the permission given herein is suspended and the fluid injection must be stopped until the fluid migration from such strata is eliminated.

APPROVED AND ISSUED ON August 28, 1987


Jerry W. Mullican
Director of Underground Injection Control